

K2 POWER ES 165K2

2-way component kit



Aluminum chassis new design

- Rigid, antimagnetic with exclusive design for a better excursion

K2 Power sandwich cone

- Dynamic & precise

Bi-Amp audiophile crossover

(Tweeter 0 / +3 / - 3 dB/oct), multi settings

- Reliability and power

Tweeter:

3 assembly solutions

- Factory location
- Flush
- In oriented pod

Integrated terminal

- More compact

Butyl surround exclusive patent "TMD" (Tuned Mass Damper) with S/N engraved

- Better control, more neutral and linear sound

TKM "M" profile aramid fiber

inverted dome tweeter

- High extension in treble
- Smooth and precision

WHAT MAKES THE DIFFERENCE

- Inverted dome "M"-shaped tweeter
- High sensitivity (92.8dB/oct)
- Bi-Amp
- Audiophile grade crossover

TECHNICAL CHARACTERISTICS

2-way component kit

Diameter: 6 1/2" (165mm)

Voice coil diameter: 1 1/4" (32mm)

Voice coil height: 0 5/8" (15mm)

Motor: Magnet

Tweeter: TKM "M" profile aramid fiber inverted dome)

Cone: Composite K2 Power "W" sandwich cone

Surround: Tuned Mass Damper (TMD®)

Separated crossover: 6-12/12dB (3.5kHz)

Tweeter Adjustable level: +3; 0; -3dB/oct

Max. power: 200W

Nom. power: 100W RMS

Sensitivity (2.83V/1m): 92.8dB

Frequency response: 60Hz- 22kHz

Impedance: 2 Ω

Accessories: Supplied grilles



Elite

"HAUTE COUTURE" SOUND



FOCAL

THE SPIRIT OF SOUND